

# Samic Optima Ferrous SAE 15W-40 CF-4

High Performance Multigrade Diesel Engine Oil

## Product Data Sheet



### Product Description & Main Application

Samic Optima Ferrous SAE 15W-40 CF-4 diesel engine oil is formulated with high quality base stocks and selected additives to ensure optimum performance and protection for diesel engines requiring an API CF-4 specification. Suitable for diesel engines for both turbocharged and normally aspirated engines operating under severe service conditions in all seasons.

### Performance & Customer Benefits

- Good oxidation & thermal stability reduces sludge build up and keeps the engine cleaner.
- Optimum wear protection to extend engine efficiency and service life.
- Improved fuel economy, due to high fluidity at low temperatures.
- Reduced oil consumption at high operating engine temperatures.
- Improved resistance to deposit formation keeps engine clean to give your vehicle maximum power under extreme operating conditions.
- Optimum TBN reserves provide improved acid neutralization and corrosion protection, especially in old heavy duty diesel engines.

### Specifications & Recommendations

**Samic Optima Ferrous SAE 15W-40 meets or exceeds following International and Builder specifications:**

- API CF-4, CF, SJ
- ACEA E2
- MTU OIL Category-1
- MAN 270/271
- VOLVO VDS
- Deutz DQC –I-05
- MB 228.0/1

### Typical Physical Characteristics

Samic Optima Ferrous SAE	Test Method	Units	15W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.884
Viscosity @ 100 °C	ASTM D 445	cSt	15.4
Viscosity @ 40 °C	ASTM D 445	cSt	120
Viscosity Index	ASTM D 2270	-	134
Pour Point	ASTM D 97	°C	-30
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	8.0
CCS Viscosity	ASTM D 5293	cP	6000 @ -20 °C

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*

For further information, please contact: [sales@samiclubricants.com](mailto:sales@samiclubricants.com)