

Samic Coast Guard 6040

High Performance Monograde - Marine Diesel Engine Cylinder Oil

Product Data Sheet



Product Description

Samic Coast Guard 6040 is extra high performance 60 TBN marine diesel engine cylinder oil formulated with premium quality base stocks and high performance additive detergent & special anti-wear technology. This cylinder oil ensures optimum performance and excellent protection in low speed 2-stroke marine diesel engines, operating on severe residual fuels & HFO with sulfur content in range of 0.5% to 3.5%. It is designed to provide excellent anti-wear properties to potentially reduce liner & ring wear and demonstrate outstanding anti-scuffing property under severe operating conditions.

Performance & Customer Benefits

- Excellent oxidation & thermal stability of oil reduces deposits formation on cylinder liners and ring belt areas.
- Outstanding anti-scuffing property provides excellent protection against ring and liner wear.
- Outstanding detergency ensures potentially cleaner pistons and liners, which helps in extending period between engine overhauling.
- Very high TBN reserves, helps in rapid neutralization of strong acidic combustion products and provides long term protection against corrosive wear of ferrous & non-ferrous metals.

Specifications & Recommendations

Samic Coast Guard 6040 meets or exceeds following International and Builder specifications:

- MAN B & W (Cross head marine diesel engine)
- Wartsila (Cross head marine diesel engine)
- Mitsubishi (Cross head marine diesel engine)

Main Application

- High TBN Cylinder oil suitable for lubricating low speed cross head diesel engines used in heavy duty marine propulsions, burning on residual fuel oils with sulfur content in range of 0.5% up to 3.5%.
- Suitable for use in latest & old model Vessels – Containers, bulkers and tankers.

Typical Physical Characteristics

Samic Coast Guard	Test Method	Units	6040
SAE Grade	--	--	40
Density @ 15 °C	ASTM D 4052	gm/cc	0.900
Viscosity @ 100 °C	ASTM D 445	cSt	15.6
Viscosity @ 40 °C	ASTM D 445	cSt	164.5
Viscosity Index	ASTM D 2270	-	96
Pour Point	ASTM D 97	°C	-9
Flash Point (COC)	ASTM D 92	°C	268
Total Base Number	ASTM D 2896	mg KOH/g	60

The above figures are typical of blends with normal production tolerance and do not constitute a specification.