

Samic Marvel Topaz 10W-40 SL/CF

Synthetic Blend - Multigrade Gasoline and Diesel Engine Oil

Product Data Sheet



Product Description

Samic Marvel Topaz 10W-40 SL/CF is designed with high quality Synthetic Blend base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise.

Performance & Customer Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.

Specifications & Recommendations

Samic Marvel Topaz meets or exceeds following International and Builder specifications:

- API SL, SJ,CF
- ACEA A3/B3
- MB Approval 229.1
- VW 505 00

Main Application

Samic Marvel Topaz is suitable for use in following:

- Automotive gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Naturally aspirated or turbo-charged engines.
- Fuel injected or indirect injection diesel engines fitted with blow-by recirculation systems.

Typical Physical Characteristics

Samic Marvel Topaz	Test Method	Units	10W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.868
Viscosity @ 100 °C	ASTM D 445	cSt	14.30
Viscosity @ 40 °C	ASTM D 445	cSt	90
Viscosity Index	ASTM D 2270	-	165
Pour Point	ASTM D 97	°C	-36
Flash Point (COC)	ASTM D 92	°C	220
Total Base Number	ASTM D 2896	mg KOH/g	9.2
Phosphorous	ASTM D 4951	% wt	0.098
CCS Viscosity	ASTM D 5293	cP	5650 @ -25 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.