

Samic Transfluid STOU series

High Performance Universal Transmission Tractor Oils



Product Data Sheet

Product Description

Samic Transfluid STOU series are extra high performance multipurpose tractor lubricants formulated from highly refined base stocks and advanced technology additive system, to meet or exceed transmission and hydraulic fluid requirements. These oils are engineered to deliver the varied lubricant performance properties required in severe duty applications of agricultural and construction equipment drive trains. Moreover it is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter.

Performance & Customer Benefits

- Excellent thermal & oxidation stability protects against deposit formation and oil thickening, thus maintains the life and performance of lubricant, seal and transmission.
- Strong anti-wear & extreme pressure properties, protects both hydraulic and gear components.
- Excellent resistance towards rust and corrosion protects equipment in wet or humid surroundings.
- Suitability for wide range of equipment simplifies the inventory.
- Improved filterability of oil keeps the system clean and operating smoothly.

Specifications & Recommendations

Samic Transfluid STOU series meets or exceeds following International and Builder specifications:

- API GL-4, CF-4
- Allison C-4
- John Deere J20C
- Denison HF-0, HF-1, HF-2 (T5D & P46 pumps)
- ZF TE-ML 03E/05F/06K/17E
- Vickers 35VQ25
- Volvo WB-101
- Caterpillar TO-2
- JI Case MS 1204-07/09
- New Holland NH 410B

Main Application

Samic Transfluid STOU series are suitable for use in:

- Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives.
- Off-highway industries including agriculture, construction, and quarrying.
- Applications requiring API GL-4 or SAE 80W grade lubricants in gear applications, except hypoid gears.

Typical Physical Characteristics

Samic Transfluid STOU	Test Method	Units	10W30	15W-40	20W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.870	0.875	0.888
Viscosity @ 40 °C	ASTM D 445	cSt	59	103	107
Viscosity @ 100 °C	ASTM D 445	cSt	9.6	14.30	14.30
Viscosity Index	ASTM D 2270	-	146	142	136
Pour Point	ASTM D 97	°C	-39	-36	-33
Flash Point (COC)	ASTM D 92	°C	212	225	230
CCS Viscosity	ASTM D 5293	cP	5550 @ -25 °C	6000 @ -20 °C	6020 @ -15 °C
Zinc	ASTM D 4951	%wt	0.12 (Min) – 0.19 (max)	0.12 (Min) – 0.19 (max)	0.12 (Min) – 0.19 (max)

The above figures are typical of blends with normal production tolerance and do not constitute a specification.

For further information, please contact: sales@Samiclubricants.com