

Samic Coast Guard 40 series

High Performance Monograde Marine Diesel Engine Oils



Product Data Sheet

Product Description

Samic Coast Guard 40 series is a range of high performance 40 TBN marine diesel engine oils formulated with premium quality base stocks and high performance additive detergent technology to ensure optimum performance and protection for highly rated trunk piston engines. They are designed to operate efficiently in severe residual-fuelled medium-speed diesel applications found in marine and stationary power industries. These TPEOs provide outstanding residual fuel compatibility and excellent engine cleanliness, especially in crankcase, camshaft areas, ring belt and piston under crowns operating under severe conditions.

Performance & Customer Benefits

- Excellent oxidation & thermal stability reduces deposits formation in piston under crown and ring belt areas.
- Outstanding protection against ring and liner wear.
- Excellent protection from rust and corrosion even in presence of water.
- Excellent oil filtration and centrifuging capabilities.
- High detergency & low dispersancy capabilities, ensures engine cleanliness and releases contaminants & water readily in centrifugal separators.
- High TBN reserves & retention, gives rapid neutralization of strong acidic combustion products and provides long term protection against corrosive wear of ferrous & non-ferrous metals.

Specifications & Recommendations

Samic Coast Guard 40 series meets or exceeds following International and Builder specifications:

- API CF

Main Application

- Suitable for lubricating Medium-speed Trunk piston engines in industrial or marine propulsion and auxiliary engines on deep sea vessels, burning on residual fuel oils with sulfur levels of 1.5% to 3.5%.
- Suitable for use in the latest model medium speed diesel engines operating with low cylinder liner temperatures.
- Marine engine reduction gears, stern tubes & bearings and certain other ship-board applications.

Typical Physical Characteristics

Samic Coast Guard	Test Method	Units	4030	4040	4050
SAE Grade	--	--	30	40	50
Density @ 15 °C	ASTM D 4052	gm/cc	0.892	0.900	0.904
Viscosity @ 100 °C	ASTM D 445	cSt	11.6	14.6	19.2
Viscosity @ 40 °C	ASTM D 445	cSt	103	145	218
Viscosity Index	ASTM D 2270	-	100	99	99
Pour Point	ASTM D 97	°C	-9	-9	-6
Flash Point (COC)	ASTM D 92	°C	245	268	276
Total Base Number	ASTM D 2896	mg KOH/g	40	40	40
Sulphated Ash	ASTM D 874	wt%	4.8	4.8	4.8

The above figures are typical of blends with normal production tolerance and do not constitute a specification.