

Samic Optima Bronze SAE 15W-40 CG-4

High Performance Multigrade Diesel Engine Oil



Product Data Sheet

Product Description & Main Application

Samic Optima Bronze SAE 15W-40 diesel engine oil is formulated with high quality base stocks and balanced additive system to ensure optimum performance and protection for diesel engines requiring an API CG-4 specification. Suitable for diesel engines fitted on trucks, buses, construction or agricultural machinery for both turbocharged and normally aspirated engines operating under severe service conditions in all seasons.

Performance & Customer Benefits

- Excellent wear protection to extend engine efficiency and service life.
- High dispersant levels in oil avoids agglomeration of combustion soot.
- Good oxidation & thermal stability reduces sludge build up and keeps the engine cleaner.
- Improved fuel economy, due to high fluidity at low temperatures.
- Reduced oil consumption at high operating engine temperatures.
- Enhanced TBN reserves provide improved acid neutralization and corrosion protection, especially in old heavy duty diesel engines.
- Improved resistance to deposit formation keeps engine clean to give your vehicle maximum power under extreme operating conditions.

Specifications & Recommendations

Samic Optima Bronze SAE 15W-40 meets or exceeds following International and Builder specifications:

- API CG-4, CF-4, CF, SJ, SL
- ACEA E3, A3, B3
- MB 228.3/229.1
- MTU OIL Category-2
- MAN 3275
- VOLVO VDS
- Deutz DQC –II-05
- Renault RD/RGD

Typical Physical Characteristics

Samic Optima Bronze SAE	Test Method	Units	15W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.884
Viscosity @ 100 °C	ASTM D 445	cSt	15.4
Viscosity @ 40 °C	ASTM D 445	cSt	120
Viscosity Index	ASTM D 2270	-	134
Pour Point	ASTM D 97	°C	-30
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	9.0
CCS Viscosity	ASTM D 5293	cP	6000 @ -20 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.