

Samic Optima Super Gold SAE 15W-40 CI-4 Plus

Enhanced High Performance Multigrade Diesel Engine Oil



Product Data Sheet

Product Description & Main Application

Samic Optima Super Gold SAE 15W-40 CI-4 Plus is high performance diesel engine oil formulated with highly refined base stocks and advanced technology additives to provide reliable performance in the latest emission designs, including those with EGR systems as per BS III/ BS IV Commercial vehicle diesel engines, as well as satisfying the needs of older engines. It may be used in naturally aspirated and turbocharged diesel and petrol engines, providing excellent protection even under the most strenuous conditions.

Performance & Customer Benefits

- Outstanding oxidation & thermal stability reduces sludge deposits and keeps the engine cleaner.
- Excellent engine protection by providing outstanding protection against wear.
- Improved fuel economy.
- Excellent dispersancy provides outstanding soot control in Exhaust Gas Recirculation (EGR) systems.
- Enhanced TBN reserves provide improved acid neutralization and corrosion protection, which helps in extending oil drain intervals.

Specifications & Recommendations

Samic Optima Super Gold SAE 15W-40 CI-4 Plus meets or exceeds following International and Builder specifications:

- API CI-4 Plus, CI-4, CH-4, CG-4, CF-4, CF, SL, SJ
- ACEA E7/A3/B4
- CAT ECF-1a, ECF-2
- MTU OIL Category 2
- MAN M3275
- VOLVO VDS-3
- Renault VI RLD-2
- Detroit Diesel 93K215
- CUMMINS CES 20076/7/20078
- Deutz DQC -III-05
- Global DHD-1
- MB 228.3/MB 229.1
- TATA Motors TSS 6576 MACK EO-N

Typical Physical Characteristics

Samic Optima Super Gold SAE	Test Method	Units	15W-40
Density @ 15 °C	ASTM D 4052	gm/cc	0.884
Viscosity @ 100 °C	ASTM D 445	cSt	15.4
Viscosity @ 40 °C	ASTM D 445	cSt	120
Viscosity Index	ASTM D 2270	-	134
Pour Point	ASTM D 97	°C	-33
Flash Point (COC)	ASTM D 92	°C	230
Total Base Number	ASTM D 2896	mg KOH/g	11.0
Sulfated Ash	ASTM D 874	% wt	1.1
CCS Viscosity	ASTM D 5293	cP	6000 @ -20 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.

For further information, please contact: sales@samiclubricants.com